

JC07 Rec'd PCT/PTO 20 DEC 2001

TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371		ATTORNEY'S DOCKET NUMBER KAK-004
		U S APPLICATION NO. If Known, see 37 CFR R-5) 10/018571
INTERNATIONAL APPLICATION NO PCT/JP00/04050	INTERNATIONAL FILING DATE 21 June 2000	PRIORITY DATE CLAIMED 21 June 1999
TITLE OF INVENTION: METHOD AND DEVICE FOR NETWORK INFERENCE		
APPLICANT(S) FOR DO/EO/US Hiroaki KITANO et al.		
Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:		
<p>1. <input checked="" type="checkbox"/> This is a FIRST submission of items concerning a filing under 35 U.S.C. 371.</p> <p>2. <input type="checkbox"/> This is a SECOND or SUBSEQUENT submission of items concerning a filing under 35 U.S.C. 371.</p> <p>3. <input checked="" type="checkbox"/> This express request to begin national examination procedures (35 U.S.C. 371(f) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(I).</p> <p>4. <input checked="" type="checkbox"/> A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.</p> <p>5. <input checked="" type="checkbox"/> A copy of the International Application as filed (35 U.S.C. 371(c)(2)) a. <input type="checkbox"/> is transmitted herewith (required only if not transmitted by the International Bureau). b. <input checked="" type="checkbox"/> has been transmitted by the International Bureau c. <input type="checkbox"/> is not required, as the application was filed in the United States Receiving Office (RO/US).</p> <p>6. <input type="checkbox"/> A translation of the International Application into English (35 U.S.C. 371(c)(2)).</p> <p>7. <input checked="" type="checkbox"/> Amendment to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3)). a. <input type="checkbox"/> are transmitted herewith (required only if not transmitted by the International Bureau). b. <input type="checkbox"/> have been transmitted by the International Bureau. c. <input type="checkbox"/> have not been made; however, the time limit for making such amendment has NOT expired. d. <input checked="" type="checkbox"/> have not been made and will not be made.</p> <p>8. <input type="checkbox"/> A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).</p> <p>9. <input type="checkbox"/> An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).</p> <p>10. <input type="checkbox"/> A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).</p> <p>Items 11 to 16 below concern either document(s) or information included:</p> <p>11. <input type="checkbox"/> In Information Disclosure Statement under 37 CFR 1.97 and 1.98.</p> <p>12. <input type="checkbox"/> An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.</p> <p>13. <input type="checkbox"/> A FIRST preliminary amendment. <input type="checkbox"/> A SECOND or SUBSEQUENT preliminary amendment.</p> <p>14. <input type="checkbox"/> A substitute specification.</p> <p>15. <input type="checkbox"/> A change of power of attorney and/or address letter.</p> <p>16. <input type="checkbox"/> Other items: Applicant claims Small Entity.</p>		

U.S. APPLICATION NO. (If known, see 37 CFR 1.5)	INTERNATIONAL APPLICATION NO. PCT/J00/04050			ATTORNEY'S DOCKET NUMBER KAK-004	
<p>17. <input checked="" type="checkbox"/> The following fees are submitted:</p> <p>Basic National Fee (37 CFR 1.49(a)(1)-(5): Search Report has been prepared by the EPO or JPO.....</p> <p>International preliminary examination fee paid to USPTO (37 CFR 1.482)</p> <p>No international preliminary examination fee paid to USPTO (37 CFR 1.482) but international search fee paid to USPTO (37 CFR 1.445(a)(2)).....</p> <p>Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO.....</p> <p>International preliminary examination fee paid to USPTO (37 CFR 1.482) and all claims satisfied provisions of PCT Article 33(2)-(4)</p>				CALCULATIONS	PTO USE ONLY
				\$ 890	
				\$ 890	
<p>Surcharge of \$130.00 for furnishing the oath or declaration later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.49(c)).</p>				\$	
Claims	Number Filled	Number Extra	Rate		
Total Claims	20=		X \$18	\$	
Independent Claims	3=		X \$84	\$	
Multiple dependent claim(s) (if applicable)				+ \$280	\$
TOTAL OF ABOVE CALCULATIONS				=	\$ 890
Reduction by $\frac{1}{2}$ for filing by small entity, if applicable Verified Small Entity statement must also be filed. (Note 37 CFR 1.9, 1.27, 1.28)				\$	
SUBTOTAL				=	\$
Processing fee of \$130.00 for furnishing the English translation later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.49(f))				\$	
TOTAL NATIONAL FEE				=	\$ 890
Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate sheet (37 CFR 3.28, 3.31) \$40.00 per property				\$	
TOTAL FEES ENCLOSED				=	\$
				Amount to be refunded	\$
				charged	\$
<p>a. <input type="checkbox"/> A check in the amount of \$_____ to cover the above fees is enclosed.</p> <p>b. <input checked="" type="checkbox"/> Please charge my Deposit Account No. <u>18-0013</u> in the amount of \$890.00 cover the above fees. A duplicate of this sheet is enclosed.</p> <p>c. <input checked="" type="checkbox"/> The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. <u>18-0013</u>. A duplicate copy of this sheet is enclosed.</p>					
<p>NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.</p>					
<p>SEND ALL CORRESPONDENCE TO Rader, Fishman & Grauer, L.P.P.C. 1233 20th Street, N.W., Suite 501 Washington, DC 20036</p>					
<p>Dated: December 20, 2001</p>					
 <u>David K. Benson</u> NAME 42,314 REGISTRATION NUMBER					

10 Recd PCT/PTO 25 APR 2002

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Attorney Docket No. KAK-004

In re patent application of

Hiroaki KITANO et al.

Serial No. 10/018,571

Group Art Unit: unassigned

Filed: December 20, 2001

Examiner: unassigned

Title: **METHOD AND DEVICE FOR NETWORK INFERENCE**

Commissioner of Patents and Trademarks
Box DAC
Washington, D.C. 20231

PRELIMINARY AMENDMENT

Sir:

Prior to the initial examination, please amend the above-identified application as follows:

IN THE CLAIMS:

Please rewrite claims 1, 9, 10 and 11 as set forth below in clean form:

1. (Amended) A network estimation method, which using at least one independent, data-generating element estimates candidate networks that are descriptive of relationships between interrelated elements as a network and that, when data generated by said elements from said network is given, are capable of reproducing data from said data given; said method comprising the steps of:

obtaining a plurality of candidate networks by producing a network structure, which may allow for reproduction of said data given, and a corresponding parameter set; and narrowing down an appropriate candidate network from said obtained networks, using

data different from said obtained data and generated from a network where a portion of the network has mutated.

9. (Deleted)

10. (Amended) A network estimation apparatus, which using at least one independent, data-generating element estimates candidate networks that are descriptive of relationships between interrelated elements as a network and that, when data generated from said network is given, are capable of reproducing said data from said data given; said network estimation apparatus comprising:

first memory means for storing a network to be configured by a network structure and corresponding parameter set;

second memory means for storing a network structure and corresponding parameter set, as a final candidate;

means for producing a network structure, which may allow for reproduction of said data given, and corresponding parameter set, and obtaining and storing in said first memory means a plurality of candidate networks; and

means for narrowing down and storing in said second memory means an appropriate candidate network from networks stored in said first memory means using data different from said obtained data and generated from a network where a portion of the network has mutated.

11. (Amended) Recording media, stored with a program capable of providing a network estimation method mentioned in any one of Claims 1 through 8 for a computer system.


R E M A R K S

This Preliminary Amendment includes the Amendment under PCT Article 34.

Additionally, in accordance with 37 CFR § 1.121(c)(1)(ii), amended claims 1, 9, 10 and 11 are set forth in a marked-up version in the pages attached hereto as APPENDIX.

If the Examiner has any suggestions for placing this application in even better form, the Examiner is invited to telephone the undersigned and the number listed below.

Respectfully submitted,



David K. Benson
Reg. No. 42,314

Date: April 25, 2002

RADER, FISHMAN & GRAUER, PLLC
The Lion Building
1233 20th Street, N.W., Suite 501
Washington, D.C. 20036
Tel: (202) 955-3750
Fax: (202) 955-3751
Customer No. 23353

APPENDIX
VERSION WITH MARKINGS TO SHOW CHANGES MADE

In the Claims:

Claims has been amended as follows:

1. A network estimation method, which using at least one independent, date-generating elements candidate networks that are descriptive of relationships between interrelated elements as a network and that, when data generated by said elements is given, are capable of reproducing data from said data given; said method comprising the steps of:

obtaining a plurality of candidate networks by producing a network structure, which may allow for reproduction of said data given, and corresponding parameter set; and

narrowing down an appropriate candidate network from said obtained networks using [other data that differs] data different from said obtained data and that can be generated from [said networks] network where a portion of the network has mutated.

9. [The network estimation method mentioned in any one of Claims 1 through 8, wherein said other data is data generated by a network, a portion of which is mutant.]

10. A network estimation apparatus, which using at least one independent, data-generating element estimates candidate networks that are descriptive of relationships between interrelated elements as a network and that, when data generated [by] from said elements is given, are capable of reproducing said data from said data given; said network estimation apparatus comprising:

first memory means for storing a network that configures a network structure and corresponding parameter set;

second memory means for storing a network structure and corresponding parameter set, as a final candidate;

means for producing a network structure, which may allow for reproduction of said data given, and corresponding parameter set, obtaining and storing in said first memory means a plurality of candidate networks; and

means for narrowing down and storing in said second memory means an appropriate candidate network from networks stored in said first memory means using [other] data different from said obtained data [that can be] and generated from a network [and that differs from said obtained data] where a portion of the network has mutated.

11. Recording media, stored with a program capable of providing a network estimation method mentioned in any one of Claims 1 through [9] 8 for a computer system.

10/018571

10 Rec'd PCT/PTO 25 APR 2002

DESCRIPTION

NETWORK ESTIMATION METHOD AND APPARATUS

Technical Field

5 The present invention relates to inverse estimation of a system that can be represented with a network model comprised of interfering discrete elements related to each other, from information representing the behavior and status of such network. In particular, it is related to estimation, from gene expression data, protein concentration data, and related data occurring in biological phenomena, of the structure, etc. of a genetic 10 control network bringing about that biological phenomenon and of a metabolic network showing reactions of enzymes and proteins.

Background Art

Due to recent rapid advances in molecular biology, much information concerning 15 major organisms is continuously being amassed. Classic examples include yeasts, nematodes, and fruit flies. For example, with nematodes (*C. elegans*), estimation of their entire cell lineage and identification of bonds in their nervous system has already been carried out, with the determination of the entire DNA base sequence being announced last year. The entire DNA base sequence of model organisms such as yeasts, *E. coli*, and

mycoplasma, and even human has also already been determined. Nevertheless, there is a large difference between knowing the DNA sequence, and understanding each gene, its function, and the interactions between genes.

Determination of such genetic functions and interactions between genes is an exceeding difficult task. A great deal of the current research in molecular biology is placing emphasis on locating genes related to noteworthy phenomena and the products of their transcription, and determination of their cascade regulation. At the stage where comprehension of the interaction between such genes takes place, understanding of complex interactions using only human intuition is extremely difficult. This is because of the large volume of data and various relationships between the interactions related to this that can be considered. We are attempting to overcome this difficulty by introducing a tool having computational ability.

This theory is expressed schematically in FIG. 1. This diagram shows the relationship between the portion using a computer (virtual portion), and the portion actually biologically tested (real portion). In FIG. 1, first, once the phenomena to be investigated is specified, based on currently known biological information (FIG. 1 PHASE I A), a model is loaded into a computer (FIG. 1 PHASE I B). In addition, in cases where a hypothesis has already been presented, that hypothesis is loaded. Using the loaded model, a simulation is performed (FIG. 1 PHASE I C), and its consistency with observed

data is subjected to verification (FIG. 1 PHASE I D). When the simulation results and observed data do not match, two possibilities can be considered. First, the simulation may not have been exact. This can be solved by improving the accuracy of the simulation and making it more reliable. The next thing to be considered is that the model may be 5 incomplete or incorrect. In this case, it is necessary to rebuild a model consistent with known test data.

Afterwards, if possible, computer testing is performed using this model (FIG. 1 PHASE II F). Actual biological testing is then begun after Phase II, or directly if Phase II is not possible, to see if the hypothetically decided models are correct (FIG. 1 PHASE III 10 and IV).

In this manner "reverse engineering of biological systems" can be carried out. Fields where it is necessary to narrow down hypothetically found models using this sort of computerized simulation, are not limited to fields of the above-mentioned organisms.

15

SUMMARY OF THE INVENTION

The object of the present invention is to efficiently narrow down hypothetically found models using a computer.

For example in the field of molecular biology, it lies in using a computer to

estimate, from such as data related to changes over time in the amount of genetic material

or protein obtained using DNA chips, microarrays, or PCR, etc., and data relating to

activity of neural networks obtained using such as electrophysiological testing or voltage

sensitive dye, a model represented with a network with interactions of genes, enzymes, or

5 proteins, and a neural network. The total number of models that can be considered from

the given data is tremendous. This has conventionally been achieved by using human

intuition to make guesses, evaluate them, and then carry out biological testing for

confirmation of their validity. The present invention tries to estimate networks that may

allow for generation of similar data, from given data by using a computer, in order to

10 measurably narrow down the number of reliable networks into a smaller number of

networks. In the case shown in the above-mentioned FIG. 1, this correlates to Phase I.

Estimation of these models of interaction (network estimation) is necessary for identifying genetic diseases and estimating the effects of medications. Furthermore, this can also be used to determine unknown genes and gene products.

15 In order to fulfill the above objective, the present invention is a method of

estimating candidate networks that are descriptive of relationships between interrelated

elements as a network and that, when data generated by said elements is given, allow for

reproduction of data from the given data; said method is characterized by comprising the

steps of producing a network structure and corresponding parameter set that may allow

for reproduction of said data, and obtaining a plurality of candidate networks; and narrowing down an appropriate candidate network from said obtained networks using other data that can be generated from a network and that differs from said obtained data.

This allows inverse estimation of a system that can be represented with a network
5 model comprised of interfering discrete elements related to each other, from data representing the behavior, status, product, etc. of such network.

When the number of network structures capable of producing said given data is small, it is possible for said step of obtaining candidate networks to include a step of producing all of those network structures.

10 Said step of obtaining candidate networks may also include a step of selecting network structures capable of reproducing said given data. This is performed in cases where there exist many networks including the parameters. Random selection of network structures, for example, can be performed for this selection step.

In cases where selection is performed in this manner, it is possible to further
15 include a step of producing with frequency network structures which reproduce data having a low margin of error with said given data.

This increases the probability of selecting networks having a high likelihood of reproducing the given data.

Furthermore, it is possible to include a step of reorganizing a portion of the

networks, which reproduce data having a low margin of error with said given data, so as to produce network structures. This can be achieved, for example, by using genetic algorithm (GA).

These network structures are obtained through a coarse, global search of the
5 network structure space.

To supplement this global search, it is possible to include, as a search to obtain a network structure, a step of searching the structural vicinities of an arbitrary network and producing a network structure. Simulated annealing (SA), for example, may be used for this local search.

10 By utilizing such a hybridization of a global search and a local search of network structures, it is possible to efficiently select an optimum network structure.

Said step of obtaining candidate networks estimates one parameter or a set of a plurality of parameters different from one another for identical network structures, and for this, estimation is performed using genetic algorithm (GA), simulated annealing (SA),
15 and/or an optimization technique such as the hill-climbing method.

Through this, it is possible to speed up estimation of optimum network structure parameters for reproduction of the given data.

In order to narrow down candidate networks obtained in this manner, data other than the given data is used; however, data generated by a network wherein a portion of the

network is mutant may be used as this data.

Thus, in the end, a comparatively small number of optimized candidate networks can be efficiently obtained.

The present invention also includes an apparatus for executing the above-
5 mentioned network estimation method and recording media stored with a program which allows a computer system to execute the network estimation method.

BRIEF DESCRIPTION OF DRAWINGS

FIG. 1 is a diagram for describing computer use in molecular biology.

10 FIG. 2 is diagrams showing an example of a genetic network; (a) is an exemplary view of a genetic network; and (b) shows a network example. In FIG. 2(b), A, B, C, and D are genetic expressions.

FIG. 3 is a diagram showing an expression profile and its corresponding network. A wild-type expression profile is shown in (a); an example where there are three nodes is shown in
15 (b); a B⁻ expression profile is shown in (c); and a C⁻ expression profile is shown in (d).

FIG. 4 is an abbreviated flow chart of an example of processing in the embodiment.

FIG. 5 is a diagram describing the fan-out limit of the network. Bonds between nodes are shown in (a). The relationship of the constraints and the probability of fan-out is shown in (b).

FIG. 6 is a selection processing flowchart and FIG. 7 is a diagram for describing a selection processing technique. In FIG. 7, n topologies, each different from the others, are randomly chosen, and the introduction of a plurality of triplets through parameter tuning using GA, SA, etc. for one of the topologies is shown. Each value of the parameter set is 5 different (For example, $P_0^0 \neq P_0^1 \neq \dots \neq P_0^M$).

FIG. 8 is a diagram describing a new search using SA. In FIG. 8 there are P triplets in the topology space and the portion within the slashed line is the portion which becomes the target of SA.

FIG. 9 is a diagram for describing selection processing of candidates, and shows the case 10 where the topology is structured from x nodes.

FIG. 10 is a diagram for describing an example of total processing of fitness, and shows an example where the sum of all degrees of fitness is assumed as the fitness of each topology.

FIGS. 11(a) and (b) are an example presented where SA is performed and a diagram showing the initial grouping.

15 FIG. 12 is a diagram showing an example of GA application. Parameters of the topology are shown in (a); and are represented by a list of bond weights and threshold values (slashed portion). Formation of the individual grouping of the second generation through mutation of the individual grouping of the first generation is shown in (b).

FIG. 13 is diagrams showing the performance of GA processing in detail. Crossover is

shown in (a) and mutation in is shown (b).

FIG. 14 is a diagram showing an example of two-dimensional GA application, wherein an example of two-dimensional GA crossover is shown. A schematic of the example shown in the bond matrix of (a) is shown in (b).

- 5 FIG. 15 is an example for describing a vicinity search using SA; wherein a state transition diagram is shown in (a), a graph of the change in state transition probability is shown in (b), and topology is shown in (c).

FIG. 16 is a flowchart showing candidate triplet selection processing using mutation.

- 10 FIG. 17 is a diagram showing an example of a genetic/metabolic network; wherein (a) is an example of codes used in a genetic/metabolic network, and (b) is an example of a network in which they are used.

FIG. 18 is a diagram showing data used in a target profile; wherein (a) is an example of zero-dimensional space data, (b) is one-dimensional space data, (c) is two-dimensional space data, and (d) is three-dimensional space data.

15

PREFERRED EMBODIMENTS OF THE PRESENT INVENTION

An embodiment of the present invention is described forthwith in detail while referencing the drawings.

The present invention can be applied to cases of estimating many different

variables determining the structure of a genetic control network bringing about a certain biological phenomena or a metabolic network showing reactions of enzymes and proteins, and reaction strength and speed, using profiles of, for example, genetic expression data or protein concentration data occurring in such phenomenon. An example in this case is 5 described below.

Genetic Network

An embodiment of the present invention is described using an example of a network showing genetic interrelations such as those shown in FIG. 2. FIG. 2(a) shows 10 the relationship showing activation of expression of material expressing the genes as nodes, and the relationship showing inhibition. The figure showing this as a network structure is FIG. 2(b). In FIG. 2(b), A, B, C, and D are types of genetic expression.

The genetic network for a given target profile (expression profile), can be represented by a “triplet”, which has three units comprising: network structure (topology), 15 which shows the reacting relationship between structural elements (DNA, RNA, proteins, etc.); a parameter set, which is a set of variables necessary when describing a model of reactions and states within the network; and degree of fitness, which shows similarity with the target profile.

To begin with, an example of a genetic network structure is described. The

reaction rules between structural elements (nodes) can be simplified and represented by N × N bond weight matrix W (parameter set) and bond matrix C (network structure). The value w of bond weight matrix W takes a real number between, for example, +1.0 and -1.0, with a negative value for w showing inhibition, and a positive value showing activation.

- 5 In bond matrix C, the two values 0 or 1 for element c_{pq} shows the bond relationship between node p and node q. 0 means that there is no bond relationship between nodes, and 1 shows that there is a bond relationship. In addition, the expressional state of a genetic network structure including N nodes occurring at time t, can be expressed with N-dimensional space vector $x(t)$. Each element of vector x is represented by $x_i(t)$ ($i = 1, \dots, N$).
- 10 If $S_i(t)$ is made the concentration of expressions of element i ($i = 1, \dots, N$), and h_i is made the threshold value determining the activation level of active elements i, each of the elements can be defined, for example, in the following manner. This function allows various definitions.

$$x_i(t+1) = F\left(\sum_{j=1}^N c_{ji} w_{ji} s_j(t) - h_i\right)$$

$$\text{here: } F(u) = \begin{cases} 0 & (u < 0) \\ u & (0 \leq u < 1) \\ 1 & (u \geq 1) \end{cases}$$

15 Outline of Processing of Embodiment

In the case of such a genetic network, given an expression profile, which is shown

as the changes in concentration of a plurality of expression materials over time, it is the object of the present invention to find a candidate genetic network expressing this expression profile. For example, the expression profile such as shown in FIG. 3(a) is given, and a candidate genetic network such as shown in FIG. 3(b) is to be found. It is noted that the expression profile shown in this FIG. 3(a) is an expression profile for a wild-type genetic structure. It is preferable that the first expression profile used be a wild type such as shown here.

The numbers of the bond (link) portions of the network show the absolute values of values w of bond weight matrix W mentioned above. It is noted here that whether the sign of value w of bond weight matrix W is negative or positive is determined by whether the bond is activation or inhibition. In addition, a mutant profile where there is no gene B and a mutant profile where there is no gene C are respectively illustrated in FIG. 3(c) and FIG. 3(d). The manner in which this profile is used is described later.

This embodiment is performed in accordance with the process shown in the abbreviated flowchart of FIG. 4. In FIG. 4, first, the structure of a network allowing the targeted expression profile to be provided is assumed, that network structure (topology) is generated, and topology pool 300 is formed (S102).

In cases where the number of network structures assumed is small, all of the network structures assumed can be generated and stored in topology pool 300; however, in

cases where the number of network structures assumed is large, it is necessary to provide certain limits for the topologies to be stored in topology pool 300.

It is noted that it is not always necessary for the topologies to be generated and stored in topology pool 300. If the topology space to be formed can be defined based on the 5 network structure assumed, an algorithm creating an arbitrary topology from this defined topology space can be utilized to achieve the same result as taking a topology from topology pool 300.

Parameters from the expression profile are adapted to each respective created topology using the degree of fitness (S104). The parameters are the values of the above-10 mentioned bond weight matrix W and a threshold value. In addition, the degree of fitness is the likelihood of these parameters (how much they match). This degree of fitness is computed using a performance function; and this performance function may be, for example, a least square error.

As described earlier, the combination of parameters and degree of fitness with the 15 network structure (topology) is referred to as a triplet (a three-point set of topology, parameters, and degree of fitness). A triplet resulting from processing is stored in triplet pool 400. When a topology is selected, parameters are adapted, and the degree of fitness is calculated, optimization is performed for a given expression profile using techniques such as GA (genetic algorithms) or SA (simulated annealing : an annealing method).

Up to this point is the stage of extracting specimens (triplets), which are objects to be processed. From this point on is the stage of narrowing down specimens (triplets) adapted for the objective from triplet pool 400. In this processing, for example, mutation analysis is utilized (S106). As a result of this processing, specimens (triplets) are 5 narrowed down, allowing an objective group of candidate triplets (candidate triplet pool 500) to be formed.

Network Extraction Process

Processing involved in generation of network structure (S102) establishes, for 10 example, the maximum assumable number of nodes included in the network. The structure of that network may be generated without any prior knowledge, or it may be generated based on a network, the structure thereof being partially known. The generated network is stored in topology pool 300. The known structure of the network in this case may have, for example, fan-out limits. This is described in FIG. 5. Fan-out 15 refers to the number of actions (activations, inhibitions) from one node to another node. FIG. 5(a) shows that there are four fan-outs from A to B through E. It is considered that the number of fan-outs has limitations, and as in the example shown in FIG. 5(b), these limitations are shown as a probability. In FIG. 5(b), it is shown that the probability of the number of fan-outs is maximized near 2, and the probability of the number of fan-outs from

5 and higher can almost be ignored. It is noted that these limitations can be defined in various ways.

In addition, in cases where already identified bonds and un-bonds are known, a network structure is produced for portions except for such bonds. When the network 5 structure is to be produced, it is possible to produce it by hypothesizing bond structures in some portions. Topologies can also be prepared by applying constraints to various structures in this manner.

Whether the parameters and the degree of fitness are adapted to all of the network structures (topologies) stored in topology pool 300 and then stored in triplet pool 10 400, or extracted and then stored, depends on the number of networks that can be generated. When there are only a few networks capable of being generated, more specifically, in cases where there are few network nodes, since it is possible to comprehensively process all of the possible networks, the parameters and the degree of fitness can be adapted to all of the generated topologies and stored in triplet pool 400. 15 However, in cases where there is an immense number of networks to generate and the total number cannot be examined, topologies are selected, parameters and degrees of fitness are apportioned, and they are stored in triplet pool 400.

Case of Many Topologies Existing

Processing occurring in cases where there is an immense number of topologies and topology selection is necessary are described forthwith in detail using the flowchart in FIG. 6, and FIG. 7 and FIG. 8.

Referring to FIG. 7 and the flowchart of FIG. 6, first, the number of topologies to be selected is determined. In this case, N topologies are said to be randomly selected. From topology pool 300 (or the topology space) of FIG. 4, one topology 310 is then randomly taken (S202). Expression parameters capable of achieving the given expression profile are then adapted to this using, for example, GA (genetic algorithm) or SA (simulated annealing) (S204). At this point, M (412, 414, 416, and 418) differing parameter sets, which have the highest degree of fitness with the given expression profile according to each expression parameter, are taken and stored in triplet pool 400. This is repeated for N topologies. During the repetition, in the step of randomly selecting a topology (S202), one of a structure differing from earlier chosen topologies is selected. At the stage where repetition is ended (YES at S206), $N \times M$ triplets are stored in triplet pool 400.

It is noted that in the above, topologies are randomly selected; however, other statistical samplings may be utilized. In addition, when M differing parameter sets are taken, the degrees of similarity among parameter sets are calculated, and when those degrees of similarity are extremely close to one another (less than a certain threshold), they may be viewed as equivalent and not selected. Since it is pointless to select a

plurality of similar solutions, this means that only a representative value is selected.

Next, N network structures (topologies), which are the N triplets stored in triplet pool 400 that have been reorganized by topology, are obtained through, for example, GA/SA (S208). As with the above, a parameter set is adapted to each of these ($N + 1$) to $2N$ topologies obtained using GA/SA, and except for the M triplets having high degrees of fitness with the expression profile, they are stored in triplet pool 400 (S210). As a result, $(2N \times M)$ triplets are stored in triplet pool 400. Of these $(2N \times M)$ triplets, P triplets having values at or below a predetermined threshold value are selected from among those having high degrees of fitness and are left in triplet pool 400 (S212). With this, there are now P triplets stored in triplet pool 400. The processing up to this point has been a global triplet search.

Local Search

The vicinities of the P triplets stored in triplet pool 400 are searched using, for example, SA (simulated annealing) to find a triplet having a higher degree of fitness (S214). This is shown in FIG. 8. FIG. 8 shows a search performed on topology space including the respective vicinities of each of the P triplets, which is a space of interest for SA. Through this, triplets having an even higher degree of fitness can be obtained. In cases where a triplet having a higher degree of fitness is found, it is also stored in triplet pool 400 (S216).

This results in P or more triplets being stored in triplet pool 400.

It is noted that at this point, in the case where a triplet having a higher degree of fitness is found in the vicinity of another triplet, that triplet is replaced and the triplet having the higher degree of fitness can be stored in triplet pool 400. In this case, the number of triplets stored in triplet pool 400 remains at P.

Here, searches are performed in the vicinities using SA; however, it is also possible for other techniques to be performed, such as the hill climbing method (a method where the most favorable point of the possible search points is selected as the search progresses).

10 As a result, since the improved degrees of fitness of the triplets are stored in triplet pool 400, at the point in time where the sampling stage ends, probability is high that the targeted triplet is among the triplets stored in triplet pool 400. Nevertheless, the number of triplets at this stage is still not low enough for biological testing to be preformed.

15

Narrowing-Down Process

Next is the stage where processing is performed to select an even smaller number of candidate triplets from the triplets stored in triplet pool 400. This processing is described forthwith using the example of FIG. 9 and FIG. 10, which uses mutation

analysis.

In FIG. 9, a mutant triplet is produced for each triplet from triplet pool 400 (S402). The mutant triplet in this case is produced by eliminating (knocking-out) a gene, and removing all of the bonds from that gene. At this point, neither the other bonds in the 5 triplet nor the parameters are changed. This is then performed for the genes (nodes of the network structure). Accordingly, of the nodes in the topology of a triplet, once each node of the respective x genes is knocked-out, it is possible to have x mutant pools 452 to 456 storing the respective mutant triplets. Each degree of fitness with each respective mutant profile, which is the given target data, is then evaluated for each mutant pool 10 (S404). Next, the degrees of fitness evaluated for each mutant pool are integrated, and ultimately, a candidate group having a degree of fitness above a certain value is chosen and stored in candidate triplet pool 500 (S406). In this case, the obtained candidate triplets may be sorted by degree of fitness, and referencing that degree of fitness, biological testing 15 can be performed starting with the highest.

Besides using the above-mentioned knocking-out for the mutation used here, any of, for example, heterozygote, over expression, or temperature sensitive mutation methods may possibly be used. For example, a heterozygote is a mutation that reduces the total amount of genetic expression by half by crushing one of the allelic genes of a specific gene locus on a homologous chromosome. In addition, over expression is a mutation which

over-expresses a certain gene. Temperature sensitive mutation is a mutation that uses a certain temperature sensitive material to halt genetic expression, or over-express, at a certain time point while taking measurements.

5 Example of Calculating Fitness Integration

This example of calculating fitness integration is described forthwith using FIG. 10. FIG. 10 shows an example where the total of the degrees of fitness of each topology of all of the mutations (including non-mutant wild-types) are handled as the fitness of that topology. In this calculation example, a simple total is done; however, depending on needs, 10 each mutation may be weighted and added.

A mutant expression profile does not always need to be obtained for all of the mutant gene networks to be examined. In this case, only the obtained mutant expression profiles are used to calculate fitness and perform integration. In this manner, candidate triplets can finally be obtained.

15

Embodiment

The above-mentioned processing is described forthwith in detail using a concrete genetic triplet example. A genetic network for achieving an expression profile, which is data in time series as shown in FIG. 3(a), is used for this example.

To begin with, coding of a chromosome is performed based on a bond matrix representative of the bond relationships of the topology. Since there are three expression materials shown in FIG. 3(a), the topology of a network with three nodes is represented by the following bond matrix C. This is shown in FIG. 3(b).

$$C = \begin{pmatrix} 1 & 1 & 0 \\ 0 & 0 & 1 \\ -1 & 0 & 0 \end{pmatrix}$$

5 Since there are bonds at four loci in this topology and it is necessary to weigh each of them, a chromosome having four genotypes is produced. Since it is also necessary to optimize the threshold value of each node, a chromosome which eventually has, in total, 4 (number of bonds) + 3 (number of node threshold values) = 7 genotypes is produced. The range (real number values) of possible threshold values and chromosome weights in this
10 case are as shown in FIG. 11(a). A plurality of such topologies capable of achieving the expression profile shown in FIG. 3(a) are produced, and stored in topology pool 300 (FIG. 4)

Optimization of parameters (weights and threshold values) is performed for each produced topology using GA. N combinations of parameters of the range determined for the topology are first generated at random, making an initial group of chromosomes. FIG.
15 11(b) shows the initial group for the topology determined by the above-mentioned bond matrix. In this manner, chromosomes are established for the topologies in a list format. Optimization is preformed by applying GA to this initial group. The degree of fitness of

each parameter is used as an index of this optimization.

The degree of fitness of the initial group is obtained by generating the expression profile at each individual piece based on the parameters of the chromosome and performing, for example, total sum square error TSS between each target profile. This 5 total sum square error TSS performs the following calculations.

As shown in FIG. 3(a), a target profile is given as time series data of concentration. For this reason, the concentration of each expression material A, B, and C occurring at time t is represented as LTA(t), LTB(t), and LTC(t), and the concentration of each expression material, which is computed using the above expression (1) based on each 10 parameter of the generated chromosomes can be represented as LEA(t), LEB(t), and LEC(t). The total sum square error TSS between these can be represented in the following manner:

$$TSS = \sum_{X}^{A,B,C} \sum_{t=0}^T (L_{TX}(t) - L_{EX}(t))^2$$

The total sum square TSS found in this manner is made to be the degree of fitness of each generated network (chromosome).

15 By using a degree of fitness found in this manner, it is possible to perform optimization for the parameters (bond weights and threshold values) of each topology using GA. This processing is described using FIG. 12 and FIG. 13 with an example where optimization is performed using GA crossover and mutation.

As shown in FIG. 12(a), the topology parameter is represented as a list of bond weights and threshold values. To begin with, an individual pair, which is to be the parents, is determined using, for example, a tournament strategy. This includes randomly selecting the number of individuals corresponding to the tournament size (for example, 2). The individual having the highest degree of fitness among the individuals selected is made one of the parents. By carrying this out one more time, the pair of parents is determined. As shown in FIG. 12(b) crossover is caused for this individual pair to generate the offspring parameters; moreover the generated parameters are then subjected to mutation; and the degree of fitness is then calculated with the generated parameters. A second generation of individual groups is obtained by performing this sort of processing until, for example, an established number of offspring are generated.

Crossover and mutation processing is described in detail using FIG. 13. In FIG. 13(a), portions 610 shown by the arrows of the parameters of Parent 1 and Parent 2 represented in the list are swapped so as to generate Child 1 and Child 2. This is the crossover processing. FIG. 13(b) shows that one of the circled parameters (bond weight 0.4) 620 of Child 1 is changed to a separate value (bond weight 0.6) 630. This change is a mutation and subjected to processing so that it occurs randomly at, for example, a fixed probability.

By repeating this crossover and mutation processing, for example, for a decided

number of generations, parameters for a certain topology can be optimized. It is noted that an elite preservation strategy can be applied to all generations. The elite preservation strategy is a technique involving passing on the individuals having the highest fitness in the group to the next generation without causing any changes through crossover and mutation.

Once the above processing has finished for all of the topologies, from this, topology sub group D+, which has a degree of fitness below the (in the case of this example, of the total sum square error) degree of fitness, is defined using the following equation.

$$D^+ = \{D^+ \in D \mid TSS(D^+) \leq T^+\}$$

The triplet (topology, parameters, and degree of fitness) of the extracted topology subgroup is stored in triplet pool 400. It is noted that optimal parameters are generated through GA for all topologies stored in topology pool 300 in this embodiment; however, in the case where the number of topologies stored in topology pool 300 is huge, the established number of topologies may be randomly selected and the parameters optimized for this may be generated using GA. Up to this point has been the global search stage.

The triplets stored in this triplet pool are further subjected to optimization using another GA technique, adding the resulting triplets. The GA applied here is a two-dimensional GA. This two-dimensional GA is described in FIG. 14. FIG. 14(a) is an example represented by a bond matrix, and the schematic thereof is shown in FIG. 14(b).

As shown in FIG. 14(a), the portions shown by the cross shape in the Parent 1 and Parent 2 bond matrix (that is, the bond relationship centered on B; see FIG. 14(b)) are subjected to crossover, and Child 1 and Child 2 are generated. In this manner, unlike with crossover on the list (parameters) described in FIG. 13(a), crossover targeting the physical structure

- 5 itself of the network is performed. Such processing is useful for optimization of a two-dimensional structure. Parameters for topologies obtained by applying two-dimensional GA are found by optimizing using GA similar to that mentioned earlier. This is executed for a decided number of generations. Then as described above, only triplets having a fitness grade of T+ or lower are further stored in triplet pool 14. It is possible to also
- 10 apply an elite preservation strategy in the additional GA processing following this.

SA (simulated annealing) is executed on triplets stored in triplet pool 400, the topology space in the vicinity of each topology is searched, and parameters optimized for the obtained topologies using GA in the same manner as earlier are found. The reason for performing searches in this vicinity is because the local searching ability of GA is inferior.

- 15 The basic SA algorithm used is as follows using a pseudo-code. This is the portion applied to each topology.

MAIN(){ INITIALIZE()

WHILE (DOES NOT SATISFY STOPPING REQUIREMENT){

```

WHILE (DOES NOT REACH THE STATE OF EQUILIBRIUM) {

    GENERATE NEXT STATE 0

    IF (ACCEPT (E, E', T))

        RENEW 0

5      }

    T= REDUCE (T)

    }

}

```

The E within the above ACCEPT (E, E', T) is a variable defining a state called
10 energy in SA, and in this case, uses the degree of fitness of each network. E' is the degree
of fitness of the triplets generated during "GENERATE NEXT STATE 0" processing. In
addition, in the SA algorithm T is a temperature parameter, and in this case, is a variable
defining a state where only this processing is used. Variable T is set to an initial value
T_{init} when processing begins. In addition, stopped state and balanced state can use, for
15 example, the processing count.

"ACCEPT (E, E', T)" and "REDUCE (T)" are defined in the following manner.

$$ACCEPT(E, E', T) = \begin{cases} 1 & E' \leq E \\ e^{-(E-E')/T} & Other \end{cases}$$

$$REDUCE(T) = \gamma T \quad (0 < \gamma \leq 1)$$

The processing represented by the above pseudo code is described forthwith.

Once the topology, which is the object of the processing, is selected, variables T and E are initialized. Then, processing is repeated a certain number of times within the defined loop, and to begin with, processing called “GENERATE NEXT STATE 0” is performed. This “GENERATE NEXT STATE 0” performs the following processing.

- 5 Based on the topology to be processed, topology with a changed bond relationship is generated. This change is based on the state transition diagram shown in FIG. 15(a), and the topology to be processed is changed according to probability P. This transitional probability is defined as the following using the above-mentioned variable T.

$$P = \begin{cases} T / T_{init} & T / T_{init} \leq \text{Threshold Value} \\ \text{Threshold Value} & \text{Other} \end{cases}$$

- Here, T is the above-mentioned variable and the threshold value is set to, for example, 0.5. The reason why the threshold value is introduced is because if the transitional probability is made very high, it would be necessary to search many changed topologies against the targeted topology, which is not a vicinity search. Since T changes at “REDUCE (T)”, which is located on the outside loop, the state transition probability does not change within the inside loop. FIG. 15(b) shows how state transition probability changes with the outside loop steps. In this case, γ is, for example, 0. 8. Changes in the topology are described with the example of topology shown in FIG. 15(c). This is the same as the topology in FIG. 3(b). It is noted that the case where state transition probability is 0.5 is described. In FIG. 15(c), since the bond from A to A is activation-

bonded, in the state transition diagram of FIG. 15(a), it is in activation state 606. From this state, only state transitions to un-bonded 604 are possible. The probability of a state transition occurring is 0.5. Next, if the bonds from A to B are looked at these are also activation-bonded, in the same manner, with a 0.5 probability, so that they may change to 5 an un-bonded state. Since the bond from B to B is in an un-bonded state, there is a 0.25 probability of state transition to an inhibition state and to an activation state each (total of 0.5). In the following manner, all of the bond relationships are changed based on the state transition diagram of FIG. 15(a) and the probability in FIG. 15(b).

In this manner, for each obtained topology, which is the result of each bond 10 relationship forming the target topology changed with the probability mentioned above in accordance with each transition diagram, optimum parameters are next determined using the above-mentioned GA, and the degree of fitness of the parameters is calculated. This generates a new triplet. At this point “GENERATE NEXT STATE ()” is completed, and the next process “ACCEPT (E, E’, T)” is executed.

15 With this “ACCEPT (E, E’, T)”, the degree of fitness (E) of the triplet having the target topology, and the degree of fitness (E’) of the generated topology are compared, and if the degree of fitness of the generated topology is low (well adapted), 1 (true) is returned. In addition, even if the generated fitness is high (not well adapted), 1 (true) is returned with a certain probability. In this case, when T is high (when there are not very many

process times), the probability of 1 (true) being returned increases. When “ACCEPT (E, E', T)” returns a 1 (true), “RENEW ()” processing is performed, and the triplet generated by “GENERATE NEXT STATE ()” is renewed.

This continues until the state of equilibrium inside the loop is obtained (in this
5 case until the number of processing times have been performed). When processing has been performed the predetermined number of times, the outside processing (“REDUCE (T)”) is performed, a new T is found, and, using this T, inside processing is performed. In this case, outside processing is also performed, for example, the predetermined times.

Then when the fitness of the triplet finally reaches $T+$, it enters the triplet pool.
10 At the time this stage ends in the above-mentioned manner, the vicinity of each topology in triplet pool 400 is searched and the replacement triplet having a more favorable fitness is stored. The processing ultimately selecting the candidate triplet from this triplet is described forthwith. This uses the expression profile of various mutations and calculates fitness with it. This processing is described using the flowchart of FIG. 16.
15 The profile as shown in FIG. 3(c) and FIG. 3(d) is first prepared according to the mutation. FIG. 3(c) and FIG. 3(d) are a mutant profile where gene B is missing and a mutant profile where gene C is missing. The respectively corresponding mutant pools are then prepared and all of the triplets within the above-mentioned triplet pool are stored in each mutant pool (S802).

The triplet topologies are made into mutant topologies for the triplets stored in each mutant pool, and using the parameters as they are, the degree of fitness with the corresponding mutant profile is calculated (S804).

- Out of the triplets in each mutant pool, those triplets with a calculated degree of fitness at or below a predetermined threshold value established for each mutation are selected (S806). Those selected triplets within each mutant pool, which are triplets common in all mutant pools and have a degree of fitness at or below a predetermined threshold level, are stored in a candidate triplet pool (S808).

With this, it is possible to decide upon appropriate candidate triplets.

10

Other Applications

- In the above description, an example of a genetic network is described; however, it can also be applied to, for example, a genetic/metabolic circuit network. FIG. 17 shows a network of a genetic/metabolic circuit. As shown in FIG. 17(a), genes, metabolic enzymes, and protein are given as nodes with the relationships between activation, inhibition, and mediation represented as links. A network using these is shown in FIG. 17(b). The processing described above can be used for the network structure shown in FIG. 17(b).

In the above, a genetic network and a metabolic circuit network are shown as a target network; however, it can also be applied to a neural circuit network as the target

network. The data (target profile) in this case would require the use of neuron activation potential.

In this manner, it is possible to use the techniques of the present invention for various objects. Various examples of applicable target profiles are shown in FIG. 18. FIG. 18(a) shows the case where the target profile is zero-dimensional space data. Examples of this data include data which fluctuates in terms of time or frequency. For example, this may be concentration, degree of activity, or electric potential. FIG. 18(b) shows one-dimensional space data. This data is of x space and of an amount dependent on time or space. This amount may be a concentration, degree of activity, or electrical potential. The target profiles shown in FIGS. 18(c) and (d) are two-dimensional space data and three-dimensional space data. These are data of an amount dependent on two dimensional (x, y) or three-dimensional (x, y, and z) space, and time or frequency. This amount may be a concentration, degree of activity, or electrical potential. As shown in FIG. 12, it is possible for a target profile to be given in various data formats.

In this manner, the present invention is effective in cases where there exists a target profile, and estimation of the network structure of that target profile is being attempted.

The present invention may be structured from not only a stand-alone computer, but is also applicable with a cluster of computers, for example a client/server system.

The structure of the present invention can be achieved by reading a program from a recording medium stored with the program related to the present invention and executing it with a system. Such a recording medium includes DVD, MD, MO, floppy disk, CD-ROM, magnetic tape, ROM cassette, etc.

5

Industrial Applicability

As described above, the present invention is extremely effective in cases where there exists data to be used as a target profile, and estimation of the network structure yielding that target profile is being attempted.

10 In particular, it can be effectively applied to model estimation in molecular biology such as with a genetic network or metabolic network.

CLAIMS

1. A network estimation method, which estimates candidate networks that are descriptive of relationships between interrelated elements as a network and that, when 5 data generated by said elements is given, are capable of reproducing data from said data given; said method comprising the steps of:

obtaining a plurality of candidate networks by producing a network structure, which may allow for reproduction of said data given, and corresponding parameter set; and narrowing down an appropriate candidate network from said obtained networks 10 using other data that differs from said obtained data and that can be generated from said networks.

2. The network estimation method mentioned in Claim 1, wherein said step of obtaining said plurality of candidate networks comprise a step of producing all of the 15 network structures capable of reproducing said data given.

3. The network estimation method mentioned in either Claim 1 or Claim 2, wherein said step of obtaining said plurality of candidate networks comprise a step of selecting a network structure capable of reproducing said data given.

4. The network estimation method mentioned in Claim 3, wherein said step of obtaining said plurality of candidate networks comprises a step of producing a network structure that reproduces, at a high frequency, data having a low margin of error with said data given.

5

5. The network estimation method mentioned in either Claim 3 or Claim 4, wherein said step of obtaining said plurality of candidate networks comprises a step of producing a network structure by reorganizing portion of the networks that reproduce data having a low margin of error with said data given.

10

6. The network estimation method mentioned in any one of Claims 3 through 5, wherein said step of obtaining said plurality of candidate networks comprises a step of producing a network structure by searching the structural vicinities of an arbitrary network.

15

7. The network estimation method mentioned in any one of Claims 1 through 6, wherein said step of obtaining said plurality of candidate networks estimates one parameter or a set of a plurality of parameters different from one another for an identical network structure.

8. The network estimation method mentioned in Claim 7, wherein said step of obtaining said plurality of candidate networks comprises a step of estimating parameters using a genetic algorithm (GA), simulated annealing (SA), and/or an optimization technique such as the hill-climbing method.

5

9. The network estimation method mentioned in any one of Claims 1 through 8, wherein said other data is data generated by a network, a portion of which is mutant.

10. A network estimation apparatus, which estimates candidate networks that are descriptive of relationships between interrelated elements as a network and that, when data generated by said elements is given, are capable of reproducing data from said data given; said network estimation apparatus comprising:

first memory means for storing a network that configures a network structure and corresponding parameter set;

15 second memory means for storing a network structure and corresponding parameter set, as a final candidate;

means for producing a network structure, which may allow for reproduction of said data given, and corresponding parameter set, obtaining and storing in said first memory means a plurality of candidate networks; and

means for narrowing down and storing in said second memory means an appropriate candidate network from networks stored in said first memory means using other data that can be generated from a network and that differs from said obtained data.

5 11. Recording media, stored with a program capable of providing a network estimation method mentioned in any one of Claims 1 through 9 for a computer system.

ABSTRACT

Topology pool 300 is produced by generating network structures (topologies) potentially being able to reproduce a target profile (S102). Best parameters to be able to 5 reproduce the target profile are determined for the respective generated network structures, and the margin of error thereof is calculated (S104). Triplets that have been combined from the parameters and the margin of error for the topologies are stored in triplet pool 400. Up to this point is the sampling stage and from this point is the stage where the triplets in triplet pool 400 adapted to the objective are screened; mutation data, 10 for example, is used for this screening (S106). Candidate triplet pool 500 is achieved once the screening stage has ended.

FIG.1





FIG.2

(a)



(b)




FIG.3





FIG.4



10/018571

FIG.5





FIG.6




FIG.7






FIG.8





FIG.9



10/018571

FIG.10

	TOPOLOGY 1	TOPOLOGY 2	· · ·	TOPOLOGY X
WILD	12	15	· · ·	32
MUTANT 1	8	6	· · ·	23
MUTANT 2	16	10	· · ·	12
	⋮	⋮	⋮	⋮
MUTANT X	13	5	· · ·	22
+)				
	382	293		512

FIG.11

(a)	CHROMOSOME BOND WEIGHT				THRESHOLD VALUE OF EACH NODE			
	A→A	A→B	B→C	C→A	A	B	C	
	[0~1]	[0~1]	[0~1]	[-1~0]	[0~1]	[0~1]	[0~1]	
<hr/>								
(b)								
INITIAL GROUP	0.2	0.4	0.2	-0.1	0.6	0.2	0.3	INDIVIDUAL 1
	0.3	0.7	0.2	-0.3	0.6	0.2	0.4	INDIVIDUAL 2
	0	0.2	0.5	-0.6	0.3	0.3	0.3	INDIVIDUAL 3
	⋮	⋮	⋮	⋮	⋮	⋮	⋮	⋮
	⋮	⋮	⋮	⋮	⋮	⋮	⋮	⋮
	⋮	⋮	⋮	⋮	⋮	⋮	⋮	⋮
	⋮	⋮	⋮	⋮	⋮	⋮	⋮	⋮
	0.3	0.2	0.6	-0.5	0.2	0.4	0.6	INDIVIDUAL N

FIG.12




FIG.13

(a)

	610				
PARENT 1	0.2	0.4	0.3 - 0.2	0.3	0.2 0.5
PARENT 2	0.1	0.2	0.2 - 0.6	0.3	0.5 0.5



CHILD 1	0.2	0.4	0.2 - 0.6	0.6	0.2 0.5
CHILD 2	0.1	0.2	0.3 - 0.2	0.3	0.5 0.5

(b)

CHILD 1 0.2 0.4 0.2 - 0.6 0.6 0.2 0.5

620



CHILD 1' 0.2 0.6 0.2 - 0.6 0.6 0.2 0.5

630

FIG.14





FIG.15






FIG.16



10 / 018571

FIG.17

(a)



(b)





FIG.18



Please type a plus sign in this box:

PTO/SB/01 (3-97)

Approved for use through 6/30/98. OMB 0651-0032
Patent and Trademark Office; US DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

DECLARATION FOR UTILITY OR DESIGN PATENT APPLICATION		Attorney Docket No.	KAK-004
		First Named Inventor	Hiroaki KITANO et al.
COMPLETE IF KNOWN			
<input checked="" type="checkbox"/> Declaration submitted with or initial filing		Application No.	10/018,571
<input type="checkbox"/> Declaration submitted after initial filing		Filing Date	
		Group Art Unit	
		Examiner Name	

As a below named inventor, I hereby declare that:

My residence, post office address, and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (only if one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

METHOD AND DEVICE FOR NETWORK INFERENCE*(Title of the Invention)*

the specification of which

- is attached hereto
or
 was filed on **June 21, 2000**, as PCT Application Number **PCT/JP/00/04050**.

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment specifically referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations § 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code §119 (a)-(d) of any foreign application(s) for patent or inventor's certificate, or § 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or of any PCT international application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application Number(s)	Country	Foreign Filing Date (MM/DD/YY)	Priority Not claimed	Certified Copy Attached YES	Certified Copy Attached NO
11-174426	Japan	June/21/1999		<input type="checkbox"/>	<input checked="" type="checkbox"/>
				<input type="checkbox"/>	<input type="checkbox"/>

 Additional foreign application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto:

I hereby claim the benefit under Title 35, United States Code §119(e) of any United States provisional application(s) listed below.

Application Number (s)	Filing Date (MM/DD/YY)	<input type="checkbox"/> Additional provisional application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

Please type a plus sign in this box:

+

PTO/SB/01 (3-97)

Approved for use through 6/30/98. OMB 0651-0032

Patent and Trademark Office; US DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

DECLARATION - Utility Or Design Patent Application

I hereby claim the benefit under Title 35, United States Code §120 of any United States application(s) or any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the matter provided by the first paragraph of Title 35, United States Code §112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations § 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

U.S Parent Application Number	PCT Parent Number	Parent Filing Date (MM/DD/YYYY)	Parent Patent Number (if applicable)

Additional U.S. or PCT international application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

As a named inventor, I hereby appoint the following registered practitioner(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith. Customer Number 23353
and

Registered practitioner(s) name/registration number listed below

Place Customer Number Bar Code Label Here

Name	Registration No.	Name	Registration No.
Richard D. Grauer	22,388	Kevin D. Rutherford	40,412
David T. Nikaido	22,663	Glenn E. Forbis	40,610
Ronald P. Kananen	24,104	Kristin L. Murphy	41,212
H. Lawrence Smith	24,900	Matthew J. Russo	41,282
Ralph T. Rader	28,772	Robert S. Green	41,800
Carl Schaukowitch	29,211	David K. Benson	42,314
Michael D. Fishman	31,951	Brian K. Dutton	47,255
Joseph V. Coppola, Sr.	33,373	Eugene G. Byrd	47,361
Michael B. Stewart	36,018		
Alexander D. Rabinovich	37,425		

Additional registered practitioner(s) named on supplemental Registered Practitioner Information sheet PTO/SB/02C attached hereto.

Direct all correspondence to Customer Number 23353 or Correspondence Address below

Name	Rader Fishman & Grauer PLLC		
Address	1233 20 th Street, N.W., Suite 501		
City, State, Zip	Washington, D.C. 20036		
Country	US	Telephone	202-955-3750

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true, and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Name of First Inventor A petition has been filed for this unsigned inventor.

Given Name (first and middle [if any])

Family Name or Surname

Hiroaki *KITANO*

Inventor's Signature	<i>Hiroaki KITANO</i>			Dated	<i>April. 1, 2002</i>	
Residence: City	Saitama	State	Country	Japan	Citizenship	Japan
Post Office Address	2-18-3, Nishikosenba-cho, Kawagoe-shi					
City	Saitama	State	Zip	350-0035	Country	Japan

Additional inventors are being named on the 1 supplemental additional inventor(s) sheet(s) PTO/SB/02A attached hereto.

Attorney Docket No. KAK-004

Please type a plus sign in this box:

+

PTO/SB/02A (3-97)

Approved for use through 6/30/98. OMB 0651-0032

Patent and Trademark Office; US DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Name of Inventor		<input type="checkbox"/> A petition has been filed for this unsigned inventor					
Given Name (first and middle [if any]) <u>Mineo</u>		Family Name or Surname <u>MOROHASHI</u>					
Inventor's Signature	<u>M. Morohashi</u>					Dated <u>3/29/02</u>	
Residence: City	<u>Tokyo</u>	State		Country	<u>Japan</u>	Citizenship	<u>Japan</u>
Post Office Address	<u>1-27-3-1010, Nishigahara, Kita-ku</u>						
City	<u>Tokyo</u>	State		Zip	<u>114-0024</u>	Country	<u>Japan</u>
Name of Inventor		<input type="checkbox"/> A petition has been filed for this unsigned inventor					
Given Name (first and middle [if any]) <u>Koji</u>		Family Name or Surname <u>KYODA</u>					
Inventor's Signature	<u>Koji Kyoda</u>					Dated <u>3/28/2002</u>	
Residence: City	<u>Kanagawa</u>	State		Country	<u>Japan</u>	Citizenship	<u>Japan</u>
Post Office Address	<u>2423-208, Nara-dho, Aoba-ku, Yokohama-shi</u>						
City	<u>Kanagawa</u>	State		Zip	<u>227-0036</u>	Country	<u>Japan</u>
Name of Inventor		<input type="checkbox"/> A petition has been filed for this unsigned inventor					
Given Name (first and middle [if any]) <u>Shugo</u>		Family Name or Surname <u>HAMAHASHI</u>					
Inventor's Signature	<u>Shugo Hamahashi</u>					Dated <u>3/29/2002</u>	
Residence: City	<u>Kanagawa</u>	State		Country	<u>Japan</u>	Citizenship	<u>Japan</u>
Post Office Address	<u>#303 Sato Bldg., 1156 Kizuki, Nakahara-ku, Kawasaki-shi</u>						
City	<u>Kanagawa</u>	State		Zip	<u>211-0025</u>	Country	<u>Japan</u>